



PINOUT	
PIN A	+12 TO +18 VDC
PIN B	PWR/SIG COM
PIN C	-12 TO -18 VDC
PIN D	EO (VOLTS/G)
PIN E	CURRENT OUTPUT
PIN F	SELF-TEST

NOTES:

- CAUTION: A .01 MF 200V CAPACITOR IS CONNECTED INTERNALLY FROM PIN B OR C TO CASE. TAKE THIS INTO ACCOUNT IF DIELECTRIC TEST IS MADE FROM PINS TO CASE. WEIGHT: 3 OZ
- BENDIX CONNECTOR PTIH-10-6P (MS311H-10-6P) MATES WITH PT06A-6S
- DATUM **- A -** AND **- B -** ARE DEFINED REFERENCE SURFACES

	DIMENSIONS UNITS ARE: [mm]	 Jewell Instruments MANCHESTER, NH TRIPLETT MODUTEC A&M EMICO	TITLE	ASBC OUTLINE DRAWING	
	TOLERANCE UNLESS SPECIFIED		DRAWING NO.	REV.	A
	TWO PLACE DECIMALS .00 ± .01	<small>PROPRIETARY NOTICE</small> THIS DRAWING IS THE PROPERTY OF JEWELL INSTRUMENTS, LLC. NEITHER THIS DOCUMENT NOR THE DATA CONTAINED HEREIN SHALL BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN AUTHORIZATION OF JEWELL INSTRUMENTS, LLC. NO RIGHT IS GRANTED TO DISCLOSE OR TO USE ANY INFORMATION CONTAINED HEREIN. ALL RIGHTS RESERVED.	SCALE	CAGE CODE	SHEET 1 OF 1
	THREE PLACE DECIMALS .000 ± .005		DO NOT SCALE	33005	
	ANGLES ± 1°				