



RS485, ASCII, MODBUS PIN ASSIGNMENT	
PIN	ASSIGNMENT
A	POWER +
B	POWER -
C	N/C
D	DATA + [RS485]
E	DATA - [RS485]
F	GND

RS232 PIN ASSIGNMENT (DO NOT EXCEED 15m (49 FT) IN CABLE LENGTH)	
PIN	ASSIGNMENT
A	POWER +
B	POWER -
C	N/C
D	RXD [RS232]
E	TXD [RS232]
F	GND

NOTES:

- UNIT IS AVAILABLE IN TWO VERSIONS; SINGLE AXIS (X AXIS), DUAL AXIS (X & Y AXIS). DUAL AXIS SHOWN HERE
- DATUM **- A -** AND **- B -** ARE DEFINED AS REFERENCE SURFACES
- CONNECTOR: PT02H-10-6P
MATES WITH: PT06A-10-6S (SR) OR EQ.

DIMENSIONS UNITS ARE: [mm] INCH TOLERANCE UNLESS SPECIFIED TWO PLACE DECIMALS .00 ± .01 THREE PLACE DECIMALS .000 ± .005 ANGLES ± 1°	 Jewell Instruments MANCHESTER, NH TRIPLETT MODUTEC A&M EMICO	TITLE JDI 6 PIN CIRC. CONN. SERIES OUTLINE DRAWING	
		DRAWING NO. OD02550414	REV. A
	PROPRIETARY NOTICE <small>THIS DRAWING IS THE PROPERTY OF JEWELL INSTRUMENTS, LLC. NEITHER THIS DOCUMENT NOR THE DATA CONTAINED HEREIN SHALL BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN AUTHORIZATION OF JEWELL INSTRUMENTS, LLC. NO RIGHT IS GRANTED TO DISCLOSE OR SO USE ANY INFORMATION CONTAINED HEREIN. ALL RIGHTS RESERVED.</small>	SCALE DO NOT SCALE	CAGE CODE 33005
		SHEET 1 OF 1	